

Professional Multi-screen Display Processor

Model: DELTA MM20NG

The most versatile architecture for video wall controllers in the industry. Highly reliable & professional solution for:

- Emergency Command Center
- Police & Traffic Control room
- Oil & Gas production control room
- Airports
- Weather monitoring Center



Specifications

*Maximum Output Capacity	HD	32
	4K	16
*Maximum Input Capacity	HD	24
	Ultra HD 4K	6
	SD Input	192
	Network Video Decoding	Up to 24 channels 1080P / 720P / D1
Available card slots	Input	12
	Output	16
Controller	Display interface	1xVGA、1xHDMI, Support external display/ touch screens
	USB port	4, Support external mouse keyboard to control the processor
	RJ45 port	1, 10 / 100M / 1000M adaptive, support other devices within the LAN remote control of the processor
	RS232 serial port	1, Support linkage control matrix, large screen and the control of access
	Processor	Intel Core i7

Specifications

Output Modules	DVI	Dual, single-link DVI-D (24 + 5), output resolution 800 * 600 ~ 1920 * 1080P optional
*Input Modules	IP	Single, RJ45 network port, single port support decoding 2-way 1080P / 720P / D1
	DVI	Dual, single-link DVI-D (24 + 5), support 800 * 600 ~ 1920 * 1080P , adaptive
	4K	2 card 1 channel, HDMI 1.4 , maximum support 3840 * 2160 @ 30Hz resolution signal input
	VGA	Dual DB-15M analog interface , support 800 * 600 ~ 1920 * 1080P , adaptive
	SDI	2 , SD / HD-SDI SMPTE 259M / 292M , support resolution : PAL / NTSC , 720P50 / 60 , 1080P25 / 30/50/60 , 1080I , etc.
Power		115VAC~230VAC 50/60Hz, Dual Redundant
Power consumption		<400W
Working Temperature		-30°C~50°C
Working Humidity		Relative humidity : 5%~95% No condensation
Height		6U
Dimension		482.5mm(W) x320mm(D) x266mm(H)
Weight		20Kg

* Customizable as per client requirement

Middle East Distributor:

Wafa Technical Systems Services, 15th floor, Prestige Tower-17, Mussafah, Abu Dhabi,

Tel: 02-5557886

Mob: 0565058258

Email: sales@wafa.ae